

CARTRIDGES POWDER-ACTUATED TOOL

Accessories and consumables compatibility



Cartridges - Propellants for powder-actuated tools

The table below provides an overview of the main Hilti cartridges and their characteristics. For more information about cartridges and power levels, please refer to section **2.5.1 Cartridges (power loads, boosters)**.

Cartridge	Color	Energy	Fastening tools			
	code*	scale*	DX 2,	DX 450, DX 460, DX 462.	DX 351	DX 860-HSN ¹
			DX 36	DX 402, DX 5		DX 9-HSN1
6.8/11M10 and 6.8/11M40 ¹	High precision					
(.27 caliber short)	brown	2 [2]				
	white [brown]	2 [2]				
	green	3 [3]				
	yellow	4 [4]				
	red	6 [5]				
	black [purple]	7 [6]				
6.8/11M10 for DX6	titanium**	6 [5]	DX6			
(.27 caliber short)	black	7 [6]	DX6			
6.8/18M10	green	3	DX 76 / DX 76 PTR			
(.27 caliber long)	yellow	4	DX 76 / DX 76 PTR			
	blue	5 [4.5]	DX 76 / DX 76 PTR			
	red	6 [5]	DX 76 / DX 76 PTR			
	black [purple]	7 [6]	DX 76 / DX 76 PTR			
6.8/18M40	blue	5 [4.5]	DX 860-ENP, DX 9-ENP			
(.27 caliber long)	red	6 [5]	DX 860-ENP, DX 9-ENP			
	black [purple]	7 [6]	DX 860-ENP, DX 9-ENP			
6.8/18	green	3	DX 600N			
(.27 caliber long)	yellow	4	DX 600N			
	red	5	DX 600N			
	black [purple]	7 [6]	DX 600N			

= compatible

* Color code and energy scale according to EN 16264, in brackets according to PATMI Training Manual.

** Hilti color code for DX6 cartridge stripe.



• All collated Hilti cartridges are available as Clean-Tec, environmentally-friendly heavy metal free cartridges except for 6.8/18 (.27 calibre long) for DX 600N tool.